

TECHNICAL DATA SHEET

P.DS.124 (FB SERIES) REV02/10/2022

WATER BASED

EASYCOAT WASHABLE MATT ACRYLIC

ISO 9001



YEAR QUALITY
GUARANTEE



Easycoat Matt is a washable, stain resistant, high hiding acrylic formulated to achieve a flawless matt finish for interior and exterior walls and ceilings.

USES

Interior & Exterior

Easycoat Matt is a washable, stain resistant, high hiding acrylic formulated to achieve a flawless matt finish for interior and exterior walls and ceilings.

FEATURES & BENEFITS

- Stain resistant
- Washable
- High hiding
- Water clean up
- Easy to apply

TECHNICAL DATA

PHYSICAL FORM	Non-flammable viscous liquid with slight ammonia odour
COLOUR	White and a range of standard colours
FINISH	Smooth Matt
SPREADING RATE	Approximately 8 - 9 m ² / ℓ per coat depending on the type of substrate, surface porosity and application method
POLYMER TYPE	Acrylic Polymer
FILLERS & PIGMENTS	Weather and light resistant types only
VISCOSITY AT 23°C	100 ± 10 KU
SG AT 23°C	1.25 ± 0.05 kg/L
SOLIDS	By Mass = 39± 2%, By Volume = 25± 2%
FILM THICKNESS	WFT = 120 - 140 µm, and DFT= 30 - 35 µm
DRYING PROPERTIES	Touch-dry: 1 hour @ 23°C
RECOATING TIME	Overcoating time: 4 hours @ 23°C
PACKAGING	5ℓ & 20ℓ
MIXING & THINNING	Stir the contents thoroughly with a flat paddle before use. No thinning is required, this product is ready for use.
CLEANING	Clean all tools (brushes, rollers & spray equipment) while wet with water after use.
APPLICATION	Apply this product with a quality brush, roller or spray equipment

Toll Free: 0800 014 901 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.124 (FB SERIES) REV02/10/2022

DO NOT PAINT

- IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
- IF IT IS RAINING OR RAIN IS FORECAST
- IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 10%)
- BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

IMPORTANT

Ensure you have enough paint to complete the task. Should different batches be used, mix together, especially for colour uniformity.

SURFACE PREPARATION

NEW SURFACES:

Ensure surfaces are dry (10% moisture maximum), in sound condition, clean and free from any contaminants such as dust, dirt, rust, salt, algae and grease.

SURFACES	PRIMER / SYSTEM
Cement plaster, Concrete-fibre cement, brick surfaces and building boards	Apply one coat of a suitable water or solvent based plaster primer and two or more coats of Easycoat Washable Matt. Optional: For optimum film build and surface finish, apply a suitable solvent based Universal Undercoat prior to application.
Gypsum plaster	Apply one coat of a suitable solvent based plaster primer and two or more coats of Easycoat Washable Matt. Optional: For optimum film build and surface finish, apply a suitable solvent based Universal Undercoat prior to application.
Metal, steel & galvanised steel	Apply one coat of a suitable metal primer (two coats at the coast), followed by a coat of a suitable solvent based Universal Undercoat and two or more coats of Easycoat Washable Matt.
Wood	Apply one coat of a suitable solvent based wood primer, then apply one coat of a suitable solvent based Universal Undercoat and two or more coats of Easycoat Washable Matt.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing any contaminants and flaking paint. Spot prime with suitable primer and finish as per NEW SURFACES table above.

HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

Toll Free: 0800 014 901 | Head Office: 012 804 7305 | www.promacpaints.co.za

