

# TECHNICAL DATA SHEET

P.DS.176 REV 00/04/2022

WATER BASED

# BRIGHT PVA

ISO 9001



QUALITY ASSURED



Promac Ecoat Bright PVA is a high hiding general purpose acrylic PVA for ceilings and surfaces where resistance to cleaning is not required.

## USES

INTERIOR / EXTERIOR

For application to suitably primed new cement plaster, concrete, brickwork and various types of building boards.

## FEATURES & BENEFITS

- Interior & Exterior
- Excellent coverage and hiding power
- Ready for use
- Easy to clean

## TECHNICAL DATA

<b>PHYSICAL FORM</b>	Non-flammable viscous liquid containing a slight ammonia odour
<b>COLOUR</b>	White & Cream
<b>FINISH</b>	Smooth, Matt
<b>SPREADING RATE</b>	Approximately 6-8 m <sup>2</sup> / litre per coat depending on the type of substrate, surface porosity and application method. Spread rates are based on the product being applied to sound smooth plaster
<b>POLYMER TYPE</b>	Acrylic Polymer
<b>FILLERS</b>	Non-toxic extenders
<b>PIGMENTS</b>	Weather and light resistant types only
<b>DRYING PROPERTIES</b>	Touch dry: 1 hour @ 23 °C Over-coating time: 4 - 6 hours @ 23 °C
<b>FLASH POINT</b>	Water based Product, Non-flammable
<b>PACKAGING</b>	20ℓ
<b>THINNING</b>	Product is ready for use
<b>MIXING</b>	Stir the contents thoroughly with a flat paddle before use
<b>CLEANING</b>	Clean all tools (brushes & rollers) while wet with water after use
<b>APPLICATION METHOD</b>	Apply this product with a paintbrush or paint roller

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | [www.promacpaints.co.za](http://www.promacpaints.co.za)



# TECHNICAL DATA SHEET

P.DS.176 REV 00/04/2022

## DO NOT PAINT

- IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
- IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
- IF IT IS RAINING OR RAIN IS FORECAST
- BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

## NEW SURFACES

Ensure surfaces are dry (15% moisture maximum), in sound condition, clean and free from any contaminants such as dust, dirt, rust, salt, algae and grease.

SURFACES	PRIMER / SYSTEM
Cement plaster, concrete, brickwork and various types of building boards	Apply one coat of a suitable plaster primer, followed by two coats of Promac Ecoat Bright PVA.

## PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dust, dirt, grease, mould, grime and flaking paint before starting to paint.

SURFACES	PRIMER / SYSTEM
Cement plaster, concrete, brickwork and various types of building boards	Spot prime bare cement plaster, concrete, brick surfaces and building boards with a suitable plaster primer followed by two coats of Promac Ecoat Bright PVA.

## IMPORTANT

This paint should not be touched up, but rather re-coat the entire panel. Plan each job carefully to avoid slight colour variations. Order enough product of the same batch number to complete the work. Alternatively premix different batches to achieve the same colour throughout. Work continuously from start to finish always keeping a wet edge to avoid panel marks and dry lines. Cutting in of corners and edges should be done as work progresses to avoid dry lines on edges and corners. Do not over-spread the product, this can produce a streaky effect. If there is any damp exceeding 15% moisture, rectify the damp or moisture and allow the surface to dry out before painting. Open-celled sponge rollers are not recommended as sagging may occur.

## HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

## DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.