

TECHNICAL DATA SHEET

P.DS.112 (FB SERIES) REV 04/04/2022

WATER BASED

PVA COATING



YEAR QUALITY



Promac Ecoat PVA is a decorative acrylic paint for interior use. May be used as a filler coating under medium quality acrylic paints on interior walls and ceilings over suitably prepared surfaces.

USES

Interior plastered or previously painted surfaces including ceilings but not recommended for potentially damp environments such as kitchens and bathrooms. May be used as a filler coating for other waterbased finishing coats such as Dimensions Matt, but not sheen finishes such as Dimensions Silk.

FEATURES & BENEFITS

- Lead content, less than 90 ppm
- Smooth, matt finish
- Easy to apply
- Water clean-up
- Easy to apply
- Water clean-up

TECHNICAL DATA

PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	White and limited range of colours
FINISH	Smooth, Matt
SPREADING RATE	Approximately 6 m ² /ℓ per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	2 – 4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	1ℓ, 5ℓ & 20ℓ
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine)
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using a Synthetic PVA roller

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.112 (FB SERIES) REV 04/04/2022

DO NOT PAINT

- IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
- IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
- IF IT IS RAINING OR RAIN IS FORECAST
- BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.