

TECHNICAL DATA SHEET

P.DS.178 REV 00/04/2022

WATER BASED
**ROOF
 & ALL**

ISO 9001



YEAR QUALITY



Promac Ecoat Roof & All is a high quality semi-matt coating for tile, cement and galvanised roofs. It is also suitable for walls, paving, waterproofing, PVC, wood and steel.

USES

EXTERIOR

Galvanized sheeting and roof tiles after suitable preparation (e.g. fibre cement, cement & ceramic types). Can also be used directly onto PVC gutters, drain-pipes, etc. Can also be used on suitably primed steel railings etc.

FEATURES & BENEFITS

- Lead content, less than 90ppm
- Weather and water resistant
- Excellent adhesion properties
- Low odour
- Alkali Resistant

TECHNICAL DATA

PHYSICAL FORM	Non-flammable viscous liquid containing a slight ammonia odour
COLOUR	Standard colours
FINISH	Semi-matt finish
SPREADING RATE	Approximately 6-8 m ² / litre per coat depending on the type of substrate, surface porosity and application method
POLYMER TYPE	Acrylic Polymer
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Touch-dry: 2 - 3 hours @ 23°C Over coating time: 4 hours @ 23°C
FLASH POINT	Water based Product, Non-flammable
PACKAGING	5l and 20l
THINNING	The product is supplied ready for use. If required use minimum amount of clean water, excessive amount can degrade the quality and performance of product
MIXING	Stir the contents thoroughly with a flat paddle before use. The product is supplied ready for use
CLEANING	Clean all tools (brushes & rollers) while wet with water after use
APPLICATION METHOD	Apply this product with a paintbrush or paint roller

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.178 REV 00/04/2022

DO NOT PAINT

- IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
- IF IT IS RAINING OR RAIN IS FORECAST
- IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
- BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

NEW SURFACES

Ensure surfaces are dry (15% moisture maximum), in sound condition, clean and free from any contaminants such as dust, dirt, rust, salt, algae and grease.

SURFACES	PRIMER / SYSTEM
Concrete, cement plaster, fibre cement, gypsum plaster, rhinolite	Apply one coat of a suitable plaster primer, followed by one coat of Ecoat Universal Undercoat and two coats of Promac Ecoat Roof & All.
New wood interior & exterior	Sand wood smooth, apply one coat of a suitable wood primer, followed by one coat of Ecoat Universal Undercoat and two coats of Promac Ecoat Roof & All.
Dry / clean / grease free mild or galvanised steel	Apply one coat of a suitable metal primer (two coats at the coast), followed by one coat of Ecoat Universal Undercoat and two coats of Promac Ecoat Roof & All.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dirt, grease, mould, grime and flaking paint before starting to paint. For porous surfaces apply one coat of a suitable bonding liquid followed by two coats of **Promac Ecoat Roof & All.** For sound surfaces apply one coat of a suitable plaster primer followed by two coats of **Promac Ecoat Roof & All.**

IMPORTANT

Ensure you have enough paint to complete the job. Should different batches be used, mix together, especially for colour uniformity.

HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.