

TECHNICAL DATA SHEET

P.DS.175 REV 00/04/2022

WATER BASED

TEXTURED COAT

ISO 9001



YEAR QUALITY



E-Coat Textured Coat is a modified acrylic wall coating with a medium textured matt finish for both interior and exterior use. Hides surface irregularities such as minor plaster defects. Long life durability with excellent UV and weather resistance, contains quartz for strength and mica for flexibility.

USES

Interior & Exterior: New or previously painted cement plaster, concrete, fibre cement, gypsum plaster, brick surfaces and building boards after suitable preparation and priming.

FEATURES & BENEFITS

- Interior & exterior
- Hides surface irregularities
- Long life durability
- Excellent UV and weather resistance
- Excellent coverage and hiding power

TECHNICAL DATA

PHYSICAL FORM	Non-flammable viscous liquid containing a slight ammonia odour
COLOUR	Standard colours
FINISH	Textured
SPREADING RATE	This product will cover approximately 3-6 m ² per litre per coat depending on the type of substrate, surface porosity and application method
POLYMER TYPE	Acrylic Polymer
PIGMENTS	Weather and light resistant types only
FILLERS	Non-toxic extenders
DRYING PROPERTIES	Touch-dry: 2 hours @ 23°C Over coating time: 4 hours @ 23°C
FLASH POINT	Water based Product, Non-flammable
PACKAGING	5ℓ and 20ℓ
THINNING	The product is supplied ready for use. If required use minimum amount of clean water, excessive amount can degrade the quality and performance of product
MIXING	Stir the contents thoroughly with a flat paddle before use.
CLEANING	Clean all tools (brushes & rollers) while wet with water after use
APPLICATION METHOD	Apply this product with a quality brush or roller to both smooth and rough surfaces in a well-ventilated area

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.175 REV 00/04/2022

DO NOT PAINT

- IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
- IF IT IS RAINING OR RAIN IS FORECAST
- IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
- BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

NEW SURFACES

Ensure surfaces are dry (15% moisture maximum), in sound condition, clean and free from any contaminants such as dust, dirt, rust, salt, algae and grease.

SURFACES	PRIMER / SYSTEM
Cement plaster, concrete, fibre cement, brick and building boards	Apply one coat of Fired Earth Plaster Primer and two coats of E-Coat Textured Coat.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dust, dirt, grease, mould, grime and flaking paint before starting to paint.

SURFACES	PRIMER / SYSTEM
Cement plaster, concrete, fibre cement, brick and building boards	Spot prime bare cement plaster, concrete, fibre cement, brick and building boards with Fired Earth Plaster Primer, followed by two coats of E-Coat Textured Coat.

IMPORTANT

This paint should not be touched up, but rather re-coat the entire panel. Plan each job carefully to avoid slight colour variations. Order enough product of the same batch number to complete the work. Alternatively premix different batches to achieve the same colour throughout. Work continuously from start to finish always keeping a wet edge to avoid panel marks and dry lines. Cutting in of corners and edges should be done as work progresses to avoid dry lines on edges and corners. Do not over-spread the product, this can produce a streaky effect. If there is any damp exceeding 15% moisture, rectify the damp or moisture and allow the surface to dry out before painting. Open-celled sponge rollers are not recommended as sagging may occur

HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.