

TECHNICAL DATA SHEET

P.DS.038 (FB-NC SERIES) REV01/05/2023

SOLVENT BASED

YES WOOD FURNITURE WAX 40



Yes Wood Furniture Wax 40 is a deep penetrating liquid wax that seeps into the wood surface to protect & feed interior woodwork. **Yes Wood Furniture Wax 40** treats & revives previously treated or coated wooden surfaces where waxes, oils, varnishes or sealers have been used. Use this product as a wipe-on maintenance and cleaning wax.

USES

INTERIOR

Compatible with most varnishes, sealers or finishes. Use as a wipe-on maintenance and cleaning wax. For use on all new, previously treated or coated interior woodwork such as wooden tables, chairs, wood panelling, wardrobes and other furniture pieces.

FEATURES & BENEFITS

- Good water repellent properties, will not crack chip or peel
- Maintenance and cleaning wax, keeping wood in pristine condition
- Deep penetrating furniture wax protects furniture and woodwork against severe moisture & environmental changes
- Easy to use, no rubbing or polishing is required; simply wipe the product on
- For use on all wood types
- High wax content enhances the natural colour & grain of wood
- Subtle waxy silk finish
- Aids the protection of furniture or woodwork while in transit
- Compatible with most varnishes, sealers or finishes
- Lead content, less than 90 ppm

TECHNICAL DATA

PHYSICAL FORM	Flammable transparent liquid
COLOUR	Clear
FINISH	Subtle waxy silk finish
VISCOSITY AT 23 °C	15 ± 10 sec FC4
SG AT 23 °C	0.77 ± 0.05 kg/L
SOLIDS	By Mass = 53± 2%, By Volume = 45± 2%
SPREADING RATE	Approximately 8 -15 m ² /ℓ per coat depending on the type of substrate, surface porosity and application method
DRYING PROPERTIES	Touch dry: 15 minutes Sanding time: 1 hour Overcoating time: 4 hours Hard dry: 16 hours
PACKAGING	1ℓ
MIXING & THINNING	Stir the contents thoroughly with a flat paddle before use. The product is ready for use; no thinning required.
CLEANING	Clean all tools while wet with mineral turpentine after use
APPLICATION METHOD	Apply using a suitable brush, super fine roller and airless spray

Toll Free: 0800 014 901 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.038 (FB-NC SERIES) REV01/05/2023

IMPORTANT

Yes Wood Furniture Wax 40 will not act as a sealer coating finish, it is a liquid maintenance and cleaning wax, keeping wood in pristine condition. Ensure that the wood is completely dry before treating it with **Yes Wood Furniture Wax 40**. In cold weather, a white solidified wax could appear. Warm container in a bowl of hot water until the white wax is fluid and shake thoroughly. Do not warm over an exposed flame or direct heat. Wax precipitates at temperatures below 10°C.

Note – not recommended to use on wooden floors because of waxy finish it became slippery.

SURFACE PREPARATION & APPLICATION

Thoroughly clean and prepare the wood surfaces by removing all dust, dirt, grease, grime, and any loose contaminants.

Wipe down the surface using Mineral Turpentine and mutton cloth, to remove dirt and grime. Multiple wipes may be required. Apply a minimum of 1-2 coats of **Yes Wood Furniture Wax 40** and up to 3 coats if extremely porous. Apply sparingly to less porous wood surfaces to avoid excess residue of product.

Previously treated or coated interior wood furniture and woodwork, where waxes, oils, varnishes, or sealers surfaces fair condition: Wipe down using Lacquer Thinners and mutton cloth, to remove dirt and grime. Multiple wipes may be required. Mechanically clean using steel wool, abrading the surface in the direction of the wood grain. Wipe down using Lacquer Thinners and mutton cloth, to remove dust and residue. Apply a minimum of 1-2 coats of **Yes Wood Furniture Wax 40** and up to 3 coats if extremely porous. Apply sparingly to less porous wood surfaces to avoid excess residue of product.

Previously treated or coated interior wood furniture and woodwork, where waxes, oils, varnishes, or sealers surfaces which are cracked, discolored, weathered, or flaking: Strip back to bare wood, either by sanding or with a Promac Strip It Paint Stripper. Rinse thoroughly with water and allow to dry. Sand to smooth finish using a 150-grit sanding paper or finer grades to produce the desired smooth surface. Remove dust, allow to dry, and treat as for new wood, before applying the selected **Yes Wood Furniture Wax 40**.

DO NOT PAINT

- If the temperature is below 10°C or above 40°C
- If the surface is damp (moisture reading above 10%)
- Surface temperature min 10°C and max 35°C
- If it is raining or rain is forecast within 6-8 hours
- Before 09h00 and after 16h00 in the winter

HEALTH & SAFETY

Keep away from heat, sparks, open flames and hot surfaces. Prohibit smoking during use. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gases, mist vapours or spray. Wash hands thoroughly after handling product. Wear protective gloves, clothing, eye protection and face protection. If swallowed, call your doctor.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

Toll Free: 0800 014 901 | Head Office: 012 804 7305 | www.promacpaints.co.za

