

# TECHNICAL DATA SHEET

P.DS.039 (FB-NC SERIES) REV01/05/2023

SOLVENT BASED

# YES WOOD WEATHERPROOF WAX 45



**Yes Wood Weatherproof Wax 45** is a UV and all weather resistant deep penetrating liquid wax that seeps into the surface to protect and feed exterior woodwork. This maintenance product treats and revives previously treated or coated wood surfaces where waxes, oils, varnishes or sealers have been used. Use **Yes Wood Weatherproof Wax 45** as a wipe-on maintenance & cleaning wax.

## USES

### Exterior

Compatible with most varnishes, sealers or finishes. Use on exterior doors, door frames, window frames, wood panelling, gates, decks and garage doors. Also for use on all new, previously treated or coated exterior wood furniture and woodwork. Use as a wipe-on maintenance and cleaning wax.

## FEATURES & BENEFITS

- Good water repellent properties; will not crack chip or peel
- Maintenance and cleaning wax, keeps wood in pristine condition
- Deep penetrating furniture wax will protect furniture and woodwork against severe moisture and environmental changes
- Easy to use – no rubbing or polishing is required; simply wipe the product on
- UV and all weather resistant
- High wax content enhances the natural colour and grain of wood
- Subtle waxy silk finish
- Protects furniture or woodwork while in transit
- For use on all wood types
- Compatible with most varnishes, sealers or finishes
- Lead content, less than 90 ppm

## TECHNICAL DATA

<b>PHYSICAL FORM</b>	Flammable transparent liquid
<b>COLOUR</b>	Clear
<b>FINISH</b>	Subtle waxy silk finish
<b>VISCOSITY AT 23 °C</b>	15 ± 10 sec FC4
<b>SG AT 23 °C</b>	0.77 ± 0.05 kg/L
<b>SOLIDS</b>	By Mass = 53± 2%, By Volume = 45± 2%
<b>SPREADING RATE</b>	Approximately 8 - 15 m <sup>2</sup> / ℓ per coat depending on the type of substrate, surface porosity and application method
<b>DRYING PROPERTIES</b>	Touch dry: 15 minutes Sanding time: 1 hour Overcoating time: 4 hours
<b>PACKAGING</b>	1ℓ
<b>MIXING &amp; THINNING</b>	Stir the contents thoroughly with a flat paddle before use. The product is ready for use.
<b>CLEANING</b>	Clean all tools while wet with mineral turpentine after use
<b>APPLICATION METHOD</b>	Apply using a suitable brush, super fine roller and airless spray

Toll Free: 0800 014 901 | Head Office: 012 804 7305 | [www.promacpaints.co.za](http://www.promacpaints.co.za)



# TECHNICAL DATA SHEET

P.DS.039 (FB-NC SERIES) REV01/05/2023

## IMPORTANT

**Yes Wood Weatherproof Wax 45** will not act as a sealer coating finish, it is a liquid maintenance & cleaning wax; keeping wood in pristine condition. Ensure that the wood is completely dry before treating it with **Yes Wood Weatherproof Wax 45**. In cold weather, a white solidified wax could appear. In this case, warm the container in a bowl of hot water until the white wax is fluid and shake thoroughly. Do not warm over an exposed flame or direct heat. Wax precipitates at temperatures below 10°C. **Yes Wood Weatherproof Wax 45** can become slippery.

Note – not recommended to use on wooden floors as the waxy finish is a poses a slipping risk.

## SURFACE PREPARATION

Thoroughly clean and prepare the wood surfaces by removing all dust, dirt, grease, grime, and any loose contaminants.

Wipe down the surface using mineral turpentine and a mutton cloth to remove dirt and grime. Multiple wipes may be required. Apply a minimum of one coat of **Yes Wood Weatherproof Wax 45**, however two coats are the standard recommendation and three coats if the surface is extremely porous. Apply sparingly to less porous wood surfaces to avoid excess residue of product.

**Previously treated or coated interior wood furniture and woodwork, where waxes, oils, varnishes, or sealers surfaces fair condition:** Wipe down using lacquer thinners and mutton cloth, to remove dirt and grime. Multiple wipes may be required. Mechanically clean using steel wool, abrading the surface in the direction of the wood grain. Wipe down using Lacquer Thinners and mutton cloth, to remove dust and residue. Apply a minimum of 1-2 coats of **Yes Wood Weatherproof Wax 45** and up to 3 coats if extremely porous. Apply sparingly to less porous wood surfaces to avoid excess residue of product.

**Previously treated or coated interior wood furniture and woodwork, where waxes, oils, varnishes, or sealers surfaces which are cracked, discolored, weathered, or flaking:** Strip back to bare wood, either by sanding or with a Promac Strip It Paint Stripper. Rinse thoroughly with water and allow to dry. Sand to smooth finish using a 150-grit sanding paper or finer grades to produce the desired smooth surface. Remove dust, allow to dry, and treat as for new wood, before applying the selected Yes Wood woodcare product.

## DO NOT USE

- If the temperature is below 10°C or above 40°C
- If the surface is damp (moisture reading above 10%)
- Surface temperature min 10°C and max 35°C
- If it is raining or rain is forecast within 6-8 hours
- Before 9h00 and after 16h00 in the winter

## HEALTH & SAFETY

Keep away from heat, sparks, open flames and hot surfaces. Prohibit smoking during use. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gases, mist vapours or spray. Wash hands thoroughly after handling product. Wear protective gloves, clothing, eye protection and face protection. If swallowed, call your doctor.

## DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.